

POWET Lite いらいきの-ST Stick Nailer 4 130mm

The 20 bar technology was first introduced by MAX in Japan in 1994 and is now available

 Light weight enables one-hand operation powered by 20 bar high pressure.



Open Nose for easy jam clearance

Just remove the nail.



APPLICATIONS

Roof ●Floor and Wall framing ●Truss framing

TOOL SPECIFICATIONS

MODEL	HS130-ST
WEIGHT	4.3 kg (9.50 lbs)
DIMENSIONS	427(H) × 85(W) × 565(L)mm
LOAD CAPACITY	64 nails
OPERATING PRESSURE	17 to 23 bar (250 to 320psi)
AIR CONSUMPTION	5.4 l/cycle at 23 bar (320psi) operating pressure
NOISE	A-weighted single-event sound power level LWA, 1s, d 101.5dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 92.0dB These values are determined and documented in accordance to EN12549:1999
VIBRATION	Vibration characteristic value = 6.6m/s² These values are determined and documented in accordance to ISO 8662-11

For the **PowerLite HS130-ST** operation, the PowerLite Compressor and PowerLite Hose are required.



isy one-hand operation

 Well-balanced HS130-ST with low recoil provides you with easy and safe operation in uneven place such as roof top.







Pointy teeth on contact arm Teeth let the user get a firm grip when toe-nailing.




Trigger Lock Dial for Safety



Maintenance free end cap filter (DEU Patent 19539950) (UK Patent 2294412)







The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



Sole NZ MAX Distributor: fastening solutions **AUCKLAND** 34 Lansford Cres Avondale Ph 09 828 2019 Fax 09 828 2017

TAURANGA 3/94 Newton Rd Mt Maunganui Ph 07 575 0088

CHRISTCHURCH 8 Holt Place Burnside Ph 03 358 8135 Fax 03 358 8930

Fax 07 5756546 sales@sifco.co.nz www.sifco.co.nz OS939NZ