

# SuperStapler

**MAX**®

**TA238B/18-6** **18GA. narrow crown staples**

**Drives 13~38mm (1/2"~1-1/2") length staples**

## FEATURES

- **Lightweight-only 1.2kg & Slim body**  
Compact and well balanced body. Easily reaches tight spots.
- **Selectable fire mechanism**  
The tool can be contact or single fired with switch lever.



- **Dial adjustable depth control**  
Dial depth control requires no special tools.

- **Belt hook**



- **staple indicator on the magazine**

## APPLICATIONS

- Door and window casings ● Plywood, decorative boards, and other interior finish works ● Panel assembly and moldings
- Sub flooring ● Furniture assembly, case back fastening, blind pinning and other finishing work ● Cabinet assembly

**Skill-Pro**



**Comes with a Plastic carry case**



## TOOL SPECIFICATIONS

PRODUCT NO.	TA238B/18-6
DIMENSIONS	241.5(H)×64(W)×231(L)mm 9-1/2"×2-1/2"×9-1/8"
WEIGHT	1.2kg (2.71lbs)
RECOMMENDED OPERATING PRESSURE	5 to 7bar (70 to 100 p.s.i.)
LOADING CAPACITY	100 Staples
AIR CONSUMPTION	0.61l(0.022ft³) at 7bar operating pressure
TECHNICAL DATA NOISE	A-weighted single-event sound power level LWA, 1s, d 87.2dB These values are determined and documented in accordance to EN12549:1999
	A-weighted single-event sound pressure level LpA, 1s, d 79.7dB
VIBRATION	2.59m/s² These values are determined and documented in accordance to ISO 8662-11
Vibration characteristic value	

## STAPLES APPLICABLE

**18 Ga. narrow crown staples**



SENCO L TYPE STAPLES

**Crown**  
6.4mm  
(1/4")

**Length**  
13mm  
(1/2")  
38mm  
(1-1/2")

**Thickness**  
1.12mm  
(.044")

**Width**  
1.25mm  
(.05")

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



Sole NZ Distributor  
**SIFCO**  
fastening solutions

AUCKLAND  
34 Lansford Cres  
Avondale  
Ph 09 828 2019  
Fax 09 828 2017

TAURANGA  
3/94 Newton Rd  
Mt Maunganui  
Ph 07 575 0088  
Fax 07 575 6546

CHRISTCHURCH  
8 Holt Place  
Burnside  
Ph 03 358 8135  
Fax 03 358 8930

www.sifco.co.nz  
sales@sifco.co.nz

OS950NZ