

Bostitch™

BCF30PTM1

Stick-Fed Cordless Nailer



AN OUTSTANDING TOOL FOR:

- Timber framing
- Particle board flooring
- Fence battens & rails
- Cement fibre board

BCF30PT nailer drives the following nails:

Code	Description	Length
IMP50R	Bright Ring shank	50mm
IMP50R330SS	Stainless Steel Ring shank	50mm
GE21	Galvanised Ring shank	50mm
GE25	Galvanised Ring shank	60mm
IMP65RGAL	Galvanised Ring shank	65mm
IMP65RSS	Stainless Steel ring shank	65mm
KC27	Bright Smooth shank	75mm
IMP75RGAL	Galvanised Ring shank	75mm
IMP88	Bright Smooth shank	88mm
IMP88GAL	Galvanised Smooth shank	88mm
IMP88RSS	Stainless Steel Ring shank	88mm

SIFCO®

fastening solutions

AUCKLAND
34 Lansford Cres
Avondale
Ph 09 828 2019
Fax 09 828 2017

TAURANGA
3/94 Newton Rd
Mt Maunganui
07 575 0088
07 575 6546

CHRISTCHURCH
8 Holt Place
Burnside
03 358 8135
03 358 8930

Email: sales@sifco.co.nz

www.sifco.co.nz

State of the Art Cordless Framing Nailer

Features:

- Cordless design for versatility.
- Adjustable depth control for counter-sinking adjustments.
- Bypass nail pusher simplifies loading.
- ABS body with belt hook/hanger.
- 20volt 4.0Ah Li-ion battery with rapid charger.
- No-mar tip & Carry bag.

Designed for versatility, the BCF30PT cordless framing nailer combines a powerful battery and good balance for best manoeuvrability and ease of operation by use of ASB plastic & alloy components.

This tool has plenty of power for framing, flooring, battening & fencing. Sequential trip operation ensures precise nail placement.



Angled magazine features fast-loading of nails by the stick and a depth control. Nails are always visible from the side so operator knows when to reload. Changing nail sizes is simple and fast, requiring no tool adjustment.

Powered by a DC brushless motor technology using a high performance 20 volt 4.0Ah Li-ion battery.

Specifications:

Length:	335mm
Height:	350mm
Width:	105mm
Weight:	3.7kg
Magazine capacity:	66 nails
Nail size range:	50-88mm
Battery:	20 volt 4.0Ah Li-ion
Re-charge time:	Less than 60 mins