

PFS50

Industrial Flooring Stapler



AN OUTSTANDING TOOL FOR:

- Domestic T & G flooring
- Sprung sports surfaces
- Commercial T & G flooring

Specifications:

Length: 465mm
Height: 480mm
Width: 80mm
Weight: 4.25kg

Air pressure: 4.9-7.1Kpa (70-100psi)
Staple capacity: 150 staples per load

SIFCO fastening solutions

AUCKLAND 34 Lansford Cres Avondale Ph 09 828 2019 Fax 09 828 2017 TAURANGA 3/94 Newton Rd Mt Maunganui 07 575 0088 07 575 6546

Email:sales@sifco.co.nz

WELLINGTON

04 568 7065

09 828 2017

CHRISTCHURCH 8 Holt Place Burnside 03 358 8135 03 358 8930

www.sifco.co.nz

MEN!

Features:

- Aluminium housing for job site durability
- High-speed mallet actuated pneumatic system
- Precisely drives staples at proper angle and depth
- Extra wide composite base plate for added stability
- Rubber headed mallet included

This air flooring stapler offers superior speed and workmanship over conventional manual fastening.

The PFS50 will drive the staples fast and accurately at the proper angle and penetration, without the danger of timber damage due to hammer marks.

To operate, simply rest the nose of the machine squarely against the work surface, the angle of staple penetration is therefore aligned. Each staple is driven with one easy tap of the hand mallet onto the top of the driving mechanism which activates the machine, driving the staple and draws the board tight simultaneously.

The PFS50 can be easily adjusted to handle different thicknesses of flooring or tongue positions.



PFS50 uses the following staples

Staple Code	Box Qty	Length
BCS4-1225	9,520	25mm
BCS4-1228	8,400	28mm
BCS4-1232	7,140	32mm
BCS4-1235	6,860	35mm
BCS4-1238-10M	10,000	38mm
BCS4-1245-10M	10,000	45mm
BCS4-1250-10M	10,000	50mm