

NEW!

SCN65C-ST Construction Coil Nailer **Coil Nailer**



Complete with blow molded case, safety glasses, oil bottle and allen keys

AN OUTSTANDING TOOL FOR:

- · Cement fibre board
- Fencing
- · Ecoply barrier and bracing
- Decking
- · Fixing to timber frame or steel frame

Specifications:

Length: 272mm Height: 295mm Width: 127mm Weight: 2.3kg Magazine capacity: 250-300 nails Air Pressure: 70-120 psi

N.Z DISTRIBUTORS OF STAPLERS & NAILERS



AUCKLAND 34 Lansford Cres Ph 09 828 2019

TAURANGA 3/94 Newton Rd Mt Maunganui 07 575 0088

CHRISTCHURCH 8 Holt Place Burnside 03 358 8135

Email:sales@sifco.co.nz www.sifco.co.nz

State of the Art

Features:

- Light-weight and easy to use
- Adjustable depth control
- Fast loading & well balanced
- Loads up to 350 nails at one time
- Precision nailing technology

Designed as a fast cycling, light-weight coil nailer for use in the construction industry.

The SCN65C-ST coil nailer drives a range of nails from 32mm up to 65mm long.

It has superior driving power and manoeuvrability with low recoil to reduce operator fatigue.

Ideal for Cement fibre board, fencing, ply bracing, decking and many other applications on construction sites.

SCN65C-ST drives Plastic & Wire welded nails:

| Product code | Туре | Shank | Length |
|----------------|-------------------|--------|--------|
| FAP32V5-H | Hardened Screw | 2.50mm | 32mm |
| FRP35V1SS | Stainless ring | 2.10mm | 35mm |
| FSP32V8HDGAL/6 | HD galv screw | 2.80mm | 32mm |
| AC38R250 | Ring | 2.50mm | 38mm |
| FAP38V5-H | Hardened Screw | 2.50mm | 38mm |
| KBP38V5GAL | Galv knurled | 2.50mm | 38mm |
| KBP38V5SS | Stainless Knurled | 2.50mm | 38mm |
| FSP40V8HDGAL/6 | HD galv screw | 2.80mm | 40mm |
| AC45R250 | Ring | 2.50mm | 45mm |
| AC50R250 | Ring | 2.50mm | 50mm |
| AC50R250HDGAL | HD galv ring | 2.50mm | 50mm |
| AC50R280HDGAL | HD galv ring | 2.80mm | 50mm |
| FAP50V5-H | Hardened Screw | 2.50mm | 50mm |
| FRP50V8HDGAL/6 | HD galv ring | 2.80mm | 50mm |
| FRP50V8SS | Stainless ring | 2.80mm | 50mm |
| FSP50V5HDGB | HD galv screw Blk | 2.50mm | 50mm |
| C50R250SS | Stainless ring | 2.50mm | 50mm |
| C50R280SS | Stainless ring | 2.80mm | 50mm |
| FAP50V5SS | Stainless screw | 2.50mm | 50mm |
| AC57R230 | Ring | 2.30mm | 57mm |
| AC57R250HDGAL | HD galv ring | 2.50mm | 57mm |
| FRP60V5HDGAL | HD galv ring | 2.50mm | 60mm |
| FRP60V5SS | Stainless ring | 2.50mm | 60mm |
| AC64R250 | Ring | 2.50mm | 64mm |
| AC64R250HDGAL | HD galv ring | 2.50mm | 64mm |
| FAP65V5HDGAL | HD galv screw | 2.50mm | 65mm |
| KBP65V5GAL | Galv knurled | 2.50mm | 65mm |
| KBP65V5SS | Stainless Knurled | 2.50mm | 65mm |