

CCA22-35 Pneumatic Carton Stapler



Actual Size



Maximum penetration Staple driven completely through two thicknesses of corrugated and clinched on underside.

Blind clinching

Easily adjustable for "blind clinching" within two thicknesses of board.

One simple adjustment controls the depth of staple penetration. With this feature you are always assured of the desired staple depth.

Specifications:

Length:
Height:
Width:
Weight:
Air Pressure:

345mm 225mm 115mm 2.10kg 70-100 PSI



AUCKLAND 34 Lansford Cres Avondale Ph 09 828 2019

sales@sifco.co.nz

TAURANGA CHRISTCHURCH 3/94 Newton Rd Mt Maunganui 07 575 0088

8 Holt Place Burnside 03 358 8135

www.sifco.co.nz

Features:

- Full cycle action for maximum speed and positive driving
- Fast, easy reloading
- Adjustable tightness of clinch
- Adjustable depth of staple penetration
- Light alloy frame for ease of handling and good balance
- Operates over a wide range of air pressures

Designed for sealing closed cartons entirely from the outside, CCA22-35 combines the speed and security of sturdy, wide-crown staple carton sealing. The magazine holds two sticks of staples, a total of 100 fasteners each load.

Adjustable depth of staple penetration and tightness of clinch results in unparalleled performance in top sealing regular slotted, full overlap, end flap, partial overlap or practically any other kind of corrugated cartons.

Loads 35/18 or 35/22LF staples with an easy adjustment of the clincher setting.



Drives the following staples:

Staple Code	Box Qty	Length
35/18 35/22LF	2,000	18mm
35/22LF	1,500	22mm