

## FSN3490-ST

### Stick-Fed Pneumatic Nailer

### Powerful light weight framing nailer



#### Features:

- Magnesium alloy body, strong and light weight.
- Dial-a-depth control for quick flush nailing adjustments.
- Moulded rubber comfort grip.
- Aggressive teeth design grips timber.
- Top loading magazine for excellent balance.
- Belt/rafter book.

The new FSN3490-ST is a light and powerful stick framing nailer for the construction industry. The magnesium alloy body is designed to be lightweight, yet highly durable.

The FSN3490-ST features a dial-a-depth control for quick and easy depth adjustment, ideal for switching from general framing to flooring or cement fibre board.

The tool offers a top loading, off-set magazine, making it easy to load, whether the user is on the ground or 30 feet up in the air.

#### AN OUTSTANDING TOOL FOR:

- Timber Framing
- Particle board flooring
- Fence battens & rails
- Cement fibre board

FSN3490-ST drives the following nails:

#### Specifications:

Length:	467mm
Height:	340mm
Width:	158mm
Weight:	3.6kg
Air pressure:	5-8Kpa, 70-120PSI
Nail size range:	50-90mm
Nail capacity:	90 nails per load

Code	Description	Length
IMP50R	Bright Ring shank	50mm
IMP50R330SS	Stainless Steel Ring shank	50mm
GE21	Galvanised Ring shank	50mm
GE25	Galvanised Ring shank	60mm
IMP65RHDGAL	Galvanised Ring shank	65mm
IMP65RSS	Stainless Ring shank	65mm
IMP75	Bright Smooth shank	75mm
IMP75RGAL	Galvanised Ring shank	75mm
IMP88	Bright Smooth shank	88mm
IMP88GAL	Galvanised Smooth shank	88mm
IMP88RSS	Stainless Steel Ring shank	88mm

# SIFCO®

fastening solutions

AUCKLAND 34 Lansford Cres Avondale Ph 09 828 2019	TAURANGA 3/94 Newton Rd Mt Maunganui 07 575 0088	CHRISTCHURCH 8 Holt Place Burnside 03 358 8135
Email: sales@sifco.co.nz		www.sifco.co.nz

#### Additional Features:

Sequential trip requires operator to hold nailer against work surface before pulling trigger. This makes accurate nail placement safer and easier.