## uperfinisher,



## NF565A/16

Drives 32 to 65mm(1-1/4" to 2-1/2") length Brad nails

## **FEATURES**

- ■Lightweight-only 1.6kg & Slim body Compact and well balanced body. Easily reaches tight spots.
- Sequential fire mechanism The tool can be contact or single fired with switch lever.





Dial adjustable depth

Dial depth control requires no special tools.

■Easy jam clearance system




Belt hook

Easy twist adjustable exhaust deflector

Exhaust air can easily be diverted 360° away from user without any tool.



- Door and window casings
  Plywood, decorative boards, and other interior finish works . Panel assembly and mouldings
- Sub flooring
  Furniture assembly, case back fastening. blind pinning and other finishing work . Cabinet assembly





The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products





PRODUCT NO.	NF565A/16	NF565A/16	
DIMENSIONS	285(H)×96(W)×297(I	285(H)×96(W)×297(L)mm (11-3/6"×3-13/16"×11-11/16")	
WEIGHT	1.6kg (3.5lbs)		
RECOMMENDED OPERATING PRESSURE	5 to 7 bar (70 to 100 p.s.i.)		
LOADING CAPACITY	100 brads	100 brads	
AIR CONSUMPTION	1.30 (0.045ft³) at 6.9 bar operating pressure		
A-weighted single-eve TECHNICAL sound power level	nt LWA,1s, d 93.3dB	These values are determined and documented in accordance to EN12549:1999	
DATA NOISE A-weighted single-event sound pressure level			
VIBRATION	5 D 111/5	3.5 m/s <sup>2</sup> These values are determined and documentedin	





Skill-Pro



AUCKLAND 34 Lansford Cres 3/94 Newton Rd Avondale

**TAURANGA** Mt Maunganui

CHRISTCHURCH 3 Industry Ave Waterloo Park Ph 09 828 2019 Ph 07 575 0088 Ph 03 358 8135

www.sifco.co.nz sales@sifco.co.nz