SuperRoote CN445R2

drives 20mm - 45mm coil nails

FEATURES



Rapid fire trigger valve CN445R2 comes with a rapid trigger valve. The CN445R2 is the fastest roofer on the market with little recoil.

Tar resistant nose (Patent pending)

The nose of the CN445R2 is designed to resist tar four times longer thanconventional tools.







Powerful

Excellent for hard dried-out wood, metal valleys and re-roofing through several layers of shingles.

Removable contact foot Easy to remove and clean, inexpensive to replace.



Nose magnet

Holds the last nail of the coil, preventing waste and jamming.



APPLICATIONS

- Asphalt shingles
 Siding
 Box assembly
- Metal to plywood

TOOL SPECIFICATIONS

MODEL CN445R2 WEIGHT 2.3Kg

DIMENSIONS 260mm x 112mm x 300mm

LOAD CAPACITY 120 Nails

OPERATING PRESSURE 700 - 100 psi (Regulator)

1.33L/cycle at 6 bar (90psi operating pressure) AIR CONSUMPTION

Only 2.3**Kg**



Full round driver blade



Dial adjustable depth control

Dial depth control requires no special tools, providing accurate depth control the softest

shingle to the hardest wood. No need to make any adjustments at the compressor.



MAX

- Comfortable rubber grip
- Trigger lock for safety

Maintenance free end cap filter (US Patent 5637125)

It prevents foreign substances from entering the tool. Internal parts last longer and the inside of the tool is kept clean. The filter has a self-cleaning feature; foreign substances are ejected automatically from the tool when



the air hose is disconnected.





Optional parts



- Vinyl Siding Kit (CN70433)
 Sequential Trigger Kit (CN80535)
 - Anti-Double Fire Trigger Kit (CN81159)



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.





AUCKLAND 34 Lansford Cres 3/94 Newton Rd Avondale Ph 09 828 2019 Ph 07 575 0088 Ph 03 358 8135

TAURANGA Mt Maunganui

CHRISTCHURCH 3 Industry Ave Waterloo Park

www.sifco.co.nz sales@sifco.co.nz