CN650M drives 27~50mm (11/8"~2") nails into 2.3~3.2mm (t) metal and also concrete

APPLICATIONS

Wood on concret fastening




Wood on metal fastening

Siding on metal stud



- Steel sheet to concrete
- Metal siding
- Wood furring to block
 - Subflooring and under-layment
 - Wall and roof sheathing
- Floor decking
- Metal sheet roofing



TOOL SPECIFICATIONS

MODEL	CN650M
WEIGHT	3.0kg (6.6 lbs)
DIMENSIONS	380(H)×132(W)×277(L)mm 15"×5-1/4"×11"
LOAD CAPACITY	200 nails
OPERATING PRESSURE	5~7kg/cm*(Regulator) 70~100p.s.i.
AIR CONSUMPTION	1.60/cycle at 6 bar (90 p.s.i.) operating pressure
NOISE	A-weighted single-event sound power level LWA, 1s, d 96.3dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 85.5dB These values are determined and documented in accordance to CEN/TC 255 WG 1 N 45.3 E. (EN-standerd in preparation)
VIBRATION	Vibration characteristic value = 4.18m/s ³ These values are determined and documented in accordance to ISO 8662-11

FEATURES

- Lightweight-only 3.0kg (6.6 lbs)
 Powerful
- Anti-double fire mechanism (UK patent 2286790)

The tool can be contact or single fired with no adjustments to tool. Simply pull the trigger then depress the contact arm and tool will contact fire. To single fire, first depress the contact arm, then pull and hold the trigger. Tool can not fire a second nail until trigger is released and tool can cycle. This is a superior safety feature.





((

 Dial adjustable depth control Dial depth control requires no special tools.






 Easy twist adjustable exhaust deflector

Exhaust air can easily be diverted 360° away from user without any tool.

Comfortable rubber grip



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



Sole NZ Distributor:

SFCO
fastening solutions

AUCKLAND

34 Lansford Cres Avondale 0600 Ph 09 828 2019 Fax 09 828 2017

TAURANGA

3/94 Newton Rd Mt Maunganui 3116 Ph 07 575 6546 Fax 07 575 6546

CHRISTCHURCH

8 Holt Place Burnside 8053 Ph 03 358 8135 Fax 03 358 8930 www.sifco.co.nz sales@sifco.co.nz

OS7118AN