



CCA22-35 Pneumatic Carton Stapler



Actual Size





Maximum penetration Staple driven completely through two thicknesses of corrugated and clinched on underside.

Blind clinching
Easily adjustable for "blind
clinching" within two
thicknesses of board.

One simple adjustment controls the depth of staple penetration. With this feature you are always assured of the desired staple depth.

Specifications:

 Length:
 340mm

 Height:
 225mm

 Width:
 115mm

 Weight:
 2.1kg

 Air Pressure:
 70-100 PSI



AUCKLAND 34 Lansford Cres Avondale Ph 09 828 2019

sales@sifco.co.nz

TAURANGA 3/94 Newton Rd Mt Maunganui 07 575 0088 CHRISTCHURCH 3 Industry Ave Waterloo Park 03 358 8135

www.sifco.co.nz

Features:

- Full cycle action for maximum speed and positive driving
- Fast, easy reloading
- Adjustable tightness of clinch
- Adjustable depth of staple penetration
- Light alloy frame for ease of handling and good balance
- Operates over a wide range of air pressures

Designed for sealing closed cartons entirely from the outside, CCA22-35 combines the speed and security of sturdy, wide-crown staple carton sealing. The magazine holds two sticks of staples, a total of 100 fasteners each load.

Adjustable depth of staple penetration and tightness of clinch results in unparalleled performance in top sealing regular slotted, full overlap, end flap, partial overlap or practically any other kind of corrugated cartons.

Loads 35/18 or 35/22LF staples with an easy adjustment of the clincher setting.



Drives the following staples:

Staple Code	Box Qty	Length
35/18	2,000	18mm
35/22LF	1,500	22mm