



FS9040-ST Pneumatic Stapler



AN OUTSTANDING TOOL FOR:

- Aluminium and joinery manufacturers.
- Sash and door mouldings.
- Cabinet manufacturers.
- Furniture manufacturers.
- Bee frame manufacturers.

Specifications:

Length: 240mm
Height: 235mm
Width: 60mm
Weight: 1.6kg
Magazine Capacity: 100
Air Pressure: 5 to 8 kpa
(77-120 psi)



AUCKLAND 34 Lansford Cres Avondale Ph 09 828 2019 TAURANGA 3/94 Newton Rd Mt Maunganui 07 575 0088 CHRISTCHURCH 3 Industry Ave Waterloo Park 03 358 8135

Email:sales@sifco.co.nz

www.sifco.co.nz

State of the Art Pneumatic Stapler

Features:

- Quick bottom loading magazine.
- Rear exhaust deflector.
- Strong and light weight die cast body.
- Cushion rubber grip.
- Sequential safety mechanism.

Designed for heavy duty use in furniture, construction, joinery and woodworking industries in many different applications.

The FS9040-ST has a bottom loading magazine which holds more than 100 narrow crown 18 gauge 90 series staples per load. Staple supply can be viewed through side window so the user can see the remaining staples.

FS9040-ST uses the following staples:

Stainless Steel	Length
416MA-S	16mm
	19mm
422MA-S	22mm
425MA-S	25mm
	28mm
432MA-S	32mm
435MA-S	35mm
438MA-S	38mm
	416MA-S 422MA-S 425MA-S 432MA-S 435MA-S

Also Divergent Point staples:

Galvanised	Stainless Steel	Length
415MA-DP	415MA-DP-S	15mm
	416MA-DP-S	16mm
418M-DP	418MA-DP-S	18mm
422MA-DP	422MA-DP-S	22mm