

CONSTRUCTION COIL NAILER



**Super Light Weight
90mm Coil Nailer**

CN890S

drives 45~90 mm (1 3/4"~3 1/2") flat wire welded nails and flat plastic sheet collated nails

360° Flexible Tailpiece



FEATURES

- Well balanced and lightest weight of this class
Weight only 3.3kg (7.3 lbs). Compact and well balanced body.
- Anti-double fire mechanism (Patent pending)
The mechanism allows both bounce firing and single-shot firing. It won't give you a double-shot when the contact arm reacts to the nailers recoil. A great safety feature!
- Runs both flat wire welded nails and plastic sheet collated nails without any adjustment
- Depth control dial
Nails depth is easily adjusted by manually turning the depth dial.
- Equipped with plastic contact tip for sheathing and decking work
- Multi-directional exhaust cover
- Built-in silencer to reduce noise level

APPLICATIONS

- Floor and wall framing. • Sub-flooring.
- Roof and wall sheathing. • Fencing.

TOOL SPECIFICATIONS

MODEL	CN890S
WEIGHT	3.3kg (7.31 lbs)
DIMENSIONS	387(H) x 129(W) x 331(L)mm 14-7/16" x 5-1/16" x 13"
LOAD CAPACITY	300 nails (Wire welded nails) 300 nails (Plastic sheet collated nails)
OPERATING PRESSURE	5-7kg/cm ² (Regulator) 70-100 p.s.i.
AIR CONSUMPTION	2.040/cycle at 6 bar (90 p.s.i.) operating pressure
NOISE	A-weighted single-event sound power level LWA, 1s, d 93.68 dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 84.88 dB These values are determined and documented in accordance to CEN/TC 255 WG 1 N 45.3 E. (EN-standard in preparation)
VIBRATION	Vibration characteristic value = 4.62m/s ² These values are determined and documented in accordance to ISO 8662-11



FASTENERS AVAILABLE

Collation type

15 degree flat wire welded nails and 15 degree flat plastic sheet collated nails.


WIRE



PLASTIC SHEET




Shank type



OPTIONAL PARTS



Flat Contact arm
(CN35644)



Support Grip
(CN35643)

The specifications and design of the products in this brochure will be subject to change without advance notice due to our continuous efforts to improve quality of our products



Sole NZ Distributor:
SIFCO
fastening solutions

AUCKLAND
34 Lansford Cres
Avondale 0600
Ph 09 828 2019
Fax 09 828 2017

TAURANGA
3/94 Newton Rd
Mt Maunganui 3116
Ph 07 575 6546
Fax 07 575 6546

CHRISTCHURCH
8 Holt Place
Burnside 8053
Ph 03 5358 8135
Fax 03 358 8930

www.sifco.co.nz
sales@sifco.co.nz

OS807AN

APPLICATIONS FOR THE MAX CN890S CONSTRUCTION COIL NAILER

WIRE COLLATED NAILS – BRIGHT STEEL, GALVANISED AND STAINLESS STEEL

<u>Application area</u>	<u>Product Code</u>	<u>Length & Description</u>	<u>Nails/coil</u>	<u>Box Size</u>
Ecoply™ Barrier/Bracing	AC45R287HDGAL	45x2.87mm Hot dip galv ring shank	250	6,000
	AC50R280HDGAL	50x2.80mm Hot dip galv ring shank	250	6,000
	C50R280SS	50x2.80mm Stainless/ring shank	225	3,600
Timber fencing	AC57R250HDGAL	57x2.50mm Hot dip galv/ring shank	250	6,000
	AC64R250HDGAL	64x2.50mm Hot dip galv/ring shank	250	6,000
Linea™	C64R280SS	64x2.80mm Stainless/ring shank	225	3,600
	AC64R290HDGAL	64x2.90mm Hot dip galv/ring shank	250	6,000
	AC75R290HDGAL	75x2.90mm Hot dip galv/ring shank	250	6,000
	AC75R306HDGAL	75x3.06mm Hot dip galv/ring shank	225	3,600
	AC90P315	90x3.15mm bright smooth shank	225	2,700
Flooring	AC64R250HDGAL	64x2.50mm Hot dip galv/ring shank	250	6,000
	C57R250SS	57x2.50mm Stainless/ring shank	225	3,600
	C64R280SS	64x2.80mm Stainless/ring shank	225	3,600
Shadowclad™ & Exterior cavity battens	AC50R280HDGAL	50x2.80mm Hot dip galv ring shank	250	6,000
	C50R280SS	50x2.80mm Stainless/ring shank	225	3,600
	C64R280SS	64x2.80mm Stainless/ring shank	225	3,600
20mm Decking – Kwila	C57R250SS	57x2.50mm Stainless/ring shank	225	3,600
20mm Decking – Pine	AC57R250HDGAL	57x2.50mm Hot dip galv/ring shank	250	6,000
40mm Decking – Pine	C75R306SS	83x3.06mm Stainless/ring shank	225	2,700
	C83R306SS	83x3.06mm Stainless/ring shank	225	2,700
Cedar weatherboard	C64R250SS	64x2.50mm Stainless/ring shank	225	3,600
Board & Batten	C83R306SS	83x3.06mm Stainless/ring shank	225	2,700

PLASTIC COLLATED GKN NAILS 7000 HOUR SALT TESTED – RUST RESISTANT

Treated ply bracing, Secret nailed Hardibacker	FSP50V5-GKN-OH	50x2.50mm GKN coated Screw shank	200	8,000
---	----------------	----------------------------------	-----	-------

PLASTIC COLLATED HARDENED NAILS – GALVANISED, STAINLESS

20m battens to masonry, metal ceiling battens, metal joist hangers, Villaboard				
	FAP45V5-H	45x2.50mm Screw shank E galv.	200	6,000
35mm battens to masonry	FAP50V5-H	50x2.50mm Screw shank E galv.	200	6,000
	FAP45V5-SS	45x2.50mm Screw shank stainless	200	4,000
	FAP50V5-SS	50x2.50mm Screw shank stainless	200	6,000
Linea face nailing	FAPC75V9HDGAL	75x2.95mm Screw shank HDGAL	200	4,000
	FAPC75V9SS	75x2.95mm Screw shank Stainless	200	4,000

PLASTIC COLLATED HOT DIP GALVANISED AND STAINLESS STEEL NAILS

Ply bracing	FRP50V8HDGAL/6	50x2.80mm Hot dip galv ring shank	250	6,000
	FRP50V8SS/8	50x2.80mm Stainless/ring shank	225	3,600
Shadowclad™ & Exterior cavity battens	FRP50V8HDGAL/6	50x2.80mm Hot dip galv ring shank	250	6,000
	FRP50V8SS/8	50x2.80mm Stainless/ring shank	225	3,600
Coloursteel roof tiles	FSP50V5HDGB	50x2.50mm screw shank HDGAL	200	6,000
Ecoply™ Barrier/Bracing	FRP50V8HDGAL/6	50x2.8mm ring shank HDGAL	200	6,000
20mm Decking Kwila/Pine	FRP60V5SS	60x2.50mm ring shank stainless	200	3,600
Fencing/Decking	FRP60V5HDGAL	60x2.50mm ring shank HDGAL	200	6,000
Wooden Weatherboards	FNR75W1HDGAL	75x3.10mm ring shank HDGAL	200	4,000
	FNR75W1SS	75x3.10mm ring shank Stainless	200	4,000
Fencing/Decking	FRJ75W1HDGAL	75x3.10mm ring shank Jolt Hd HDGAL	200	4,000
	FRJ75W1SS	75x3.10mm ring shank Jolt Stainless	200	4,000
	FSJ75W1HDGAL	75x3.10mm screw shank Jolt HDGAL	200	4,000