Bostitch_™ F28WW-2

Pneumatic Framing Nailer



AN OUTSTANDING TOOL FOR:

- Timber framing
- Particle board flooring
- Fence battens & rails
- Cement fibre board
- Cavity battens

F28WW-2 drives wire welded stick nails

| Bright Steel | Galvanised | Stainless Steel | Length |
|-----------------|--------------|--------------------|--------|
| S50R287 | S50R287HDGAL | | 50mm |
| | S60R280HDGAL | | 60mm |
| S65P287 | | S65R306SS | 65mm |
| S75P306 | S75R306HDGAL | S75R306SS | 75mm |
| S90P315 | S90R315HDGAL | S90R315SS | 90mm |
| S90P333 | | | |

State of the Art

Features:

- Lightweight magnesium body
- Adjustable depth control for counter-sinking adjustments.
- Bypass nail pusher simplifies loading
- Rubber grip & belt hook/hanger
- Adjustable exhaust
- Rugged long life design
- No-mark plastic tip

Designed for versatility, the F28WW-2 air framing nailer combines light weight and good balance for best manoeuvrability and ease of operation by use of Magnesium & Alloy components.

This tool has plenty of power for framing, flooring, battening & fencing. The Sequential trip operation ensures precise nail placement.

The angled magazine features fast-loading of nails by the stick and a depth control. Nails are always visible from the side so operator knows when to reload. Changing nail sizes is simple and fast, requiring no tool adjustment. This tool does not require regular maintenance if lubricated frequently.

| Specifications | | | | |
|--------------------|-----------|--|--|--|
| Length: | 330mm | | | |
| Height: | 387mm | | | |
| Width: | 108mm | | | |
| Weight: | 3.5kg | | | |
| Magazine capacity: | 100 nails | | | |

